Printing date 03/20/2019

Reviewed on 03/20/2019

1 Identification

- · Product identifier
- · Trade name: SILPRO BCA
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SILPRO LLC 2 New England Way Ayer,MA 01432
- Emergency telephone number: CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2

H351 Suspected of causing cancer.

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: ethyl acrylate
- 1,2-benzisothiazol-3(2H)-one
- Hazard statements May cause an allergic skin reaction. Suspected of causing cancer.
- · Precautionary statements
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin: Wash with plenty of water.
- IF exposed or concerned: Get medical advice/attention.
- Specific treatment (see on this label).
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 03/20/2019

Reviewed on 03/20/2019

Trade name: SILPRO BCA

(Contd. of page 1)

38.88%

1.4%

0.06%

Classification system:
 NFPA ratings (scale 0 - 4)

000

Health = 0 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTHImage: Constraint of the sector with the sector

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

•	Dangerous	components:
---	-----------	-------------

1332-58-7 Kaolin

140-88-5 ethyl acrylate

2634-33-5 1,2-benzisothiazol-3(2H)-one

4 First-aid measures

· Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 03/20/2019

(Contd. of page 2)

Trade name: SILPRO BCA

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Not required.
 Environmental precautions: Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

• Protective A

1 AV-1.		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	140 mg/m ³
140-88-5	ethyl acrylate	8.3 ppm
57-13-6	urea	30 mg/m ³
141-43-5	2-aminoethanol	6 ppm
9016-45-9	nonylphenolethoxylates	43 mg/m ³
· PAC-2:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m ³
140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m ³
141-43-5	2-aminoethanol	170 ppm
9016-45-9	nonylphenolethoxylates	470 mg/m ³
· PAC-3:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	8,900 mg/m³
140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m ³
141-43-5	2-aminoethanol	1,000 ppm
9016-45-9	nonylphenolethoxylates	5,400 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.

(Contd. on page 4)

JS

Reviewed on 03/20/2019

(Contd. of page 3)

Printing date 03/20/2019

Trade name: SILPRO BCA

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

1332-58-7 Kaolin

- PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
- TLV Long-term value: 2* mg/m³ E; as respirable fraction

140-88-5 ethyl acrylate

- PEL Long-term value: 100 mg/m³, 25 ppm Skin
- REL See Pocket Guide App. A
- TLV Short-term value: 61 mg/m³, 15 ppm Long-term value: 20 mg/m³, 5 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to

Printing date 03/20/2019

Trade name: SILPRO BCA

(Contd. of page 4)

be checked prior to the application. • **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

General Information Appearance:	
Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.3 %
Water:	28.4 %
VOC content:	0.32 %
	3.2 g/l / 0.03 lb/gal

Printing date 03/20/2019

Reviewed on 03/20/2019

(Contd. of page 5)

Trade name: SILPRO BCA

• Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 57,143 mg/kg (rat)

Dermal LD50 131,000 mg/kg (rabbit)

Inhalative LC50/4 h 155,714 mg/l (rat)

140-88-5 ethyl acrylate

OralLD50800 mg/kg (rat)DermalLD501,834 mg/kg (rabbit)InhalativeLC50/4 h2,180 mg/l (rat)

Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

 140-88-5
 ethyl acrylate

 · NTP (National Toxicology Program)

 None of the ingredients is listed.

 · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

2B

US

Printing date 03/20/2019

Reviewed on 03/20/2019

(Contd. of page 6)

Trade name: SILPRO BCA

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA Class	not regulated	
Packing group DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.	
UN "Model Regulation":	not regulated	

(Contd. on page 8)

119

Printing date 03/20/2019

Reviewed on 03/20/2019

Trade name: SILPRO BCA

(Contd. of page 7)

10041104	Ith and environmental regulations/legislation specific for the substance or m c Substances Control Act):	
1332-58-7	•	
	Distillates (petroleum), hydrotreated heavy naphthenic	
	Petroleum Hydrocarbon Resin	
	ethyl acrylate	
57-13-6	urea	
141-43-5	2-aminoethanol	
	nonylphenolethoxylates	
	1,2-benzisothiazol-3(2H)-one	
	water, distilled, conductivity or of similar purity	
Propositio		
	known to cause cancer:	
140-88-5 e	hyl acrylate	
Chemicals	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	ingredients is listed.	
Carcinoge	nic categories	
	onmental Protection Agency)	
-		
57-13-6 ure		
	hold Limit Value established by ACGIH)	
TLV (Thres	hold Limit Value established by ACGIH) Kaolin	
TLV (Thres 1332-58-7	Kaolin	
TLV (Thres 1332-58-7 140-88-5	Kaolin ethyl acrylate	
TLV (Thres 1332-58-7 140-88-5 NIOSH-Ca	Kaolin ethyl acrylate National Institute for Occupational Safety and Health)	
TLV (Thres 1332-58-7 140-88-5 NIOSH-Ca 140-88-5	Kaolin ethyl acrylate National Institute for Occupational Safety and Health) thyl acrylate	
TLV (Thres 1332-58-7 140-88-5 NIOSH-Ca 140-88-5 GHS label	Kaolin ethyl acrylate National Institute for Occupational Safety and Health) thyl acrylate elements is classified and labeled according to the Globally Harmonized System (GHS).	
TLV (Thres 1332-58-7 140-88-5 NIOSH-Ca 140-88-5 GHS label The product Hazard pict	Kaolin ethyl acrylate National Institute for Occupational Safety and Health) thyl acrylate elements is classified and labeled according to the Globally Harmonized System (GHS).	

• Hazard statements May cause an allergic skin reaction. Suspected of causing cancer.

Printing date 03/20/2019

Reviewed on 03/20/2019

Trade name: SILPRO BCA

(Contd. of page 8)

Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Technical Department · Contact: Technical Director · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2

US -