



SILPRO

FLOOR PREPARATION AND
CONCRETE REPAIR PRODUCTS



SILPRO is committed to being the leader in product availability and responding to customers' needs that sets the standard for the industry.



ABOUT SILPRO

SILPRO remains dedicated to providing meaningful value to our Floor Preparation, Concrete Repair, and Masonry customers through product depth, performance, and availability - all at a competitive price and backed by superior technical support and personalized service. Time is short, speed is essential!

WHY SILPRO?

Because with today's complex projects and fast-track schedules, you need the peace of mind that Silpro provides. Silpro has earned our customer's trust by creating reliable solutions that improve service life, and reduce cost and conflicts. Silpro remains committed to bringing compelling value to our Flooring and Concrete Restoration contractors by offering consistently high quality and competitively priced products with unsurpassed knowledge, service and technical support. Faster. Better. Done.

THE SILPRO COMMITMENT

The growth and success of our customers is our highest priority. In conjunction with our distributor partners, we strive to provide you with meaningful value through product depth, performance, and availability.



PRODUCT USAGE GROUPS



SKIM COATS

6

PRIME PATCH® - PRIME PATCH® 20 - SKIM PRO®

REPAIR MORTARS - THIN

7

FASCO® - MASCO™ - PATCHCO® - TDQ THIN DEEP QUICK REPAIR™

REPAIR MORTARS - THICK

9

FASTCRETE® - MASCRETE®/R-50™ - SILPRORAPID™

SELF-LEVELING CEMENTS

10

SLU SUPERFLOW™ - SILFLO® 230/SLT™ - SILFLO® 220 - SILFLO® SG

EPOXY BONDING AGENT AND MOISTURE MITIGATION

11

CIE 100 EPOXY™

VERTICAL AND OVERHEAD MORTARS

11

EASY PATCH® - SILPROREPAIR® VOH - VO PATCH®

DECORATIVE EXTERIOR FINISHES

12

CALIFORNIA STUCCO™ - CONCRETE FINISH™ - FSB FIBERGLASS SURFACE BONDING CEMENT® - SKIMWALL™ - SILPROFINISH COTE™

WATERPROOFING CEMENTS

14

SEAL COTE®

GROUT

15

SILPROGROUT® 424 - SILPROGROUT® UWR

HYDRAULIC PLUGS

15

EASY PLUG®

POLYMERIC JOINT SAND

15

SILPROPAVER® SAND

BONDING AGENTS AND ADMIXTURES

16

C-21 ALL ACRYLIC®/R-50 LATEX™ - CONCRETE SUPPLEMENT™ - R-2000 PRIMER™
R-3000 PRIMER™ - WELD-O-BOND™

BONDING AGENTS AND ADMIXTURES

19

MASONRY LUSTA PLUS® GLOSS AND MATTE - SILOCKS PLUS® - SILOCKS PLUS® WB



SKIM COATS



PRIME PATCH®

Category:	Skim Coats	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	15 min set	25# bag	120
Thickness:	Featheredge to 1/2 inch			
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Thin skim coat prior to finished flooring			

PRIME PATCH® 20

Category:	Skim Coats	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	20 min set	25# bag	120
Thickness:	Featheredge to 1/2 inch	20 min set	45# pail	36
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Thin skim coat prior to finished flooring			

SKIM PRO®

Category:	Skim Coats	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Fast set	10# bag	200
Thickness:	Featheredge to 1/2 inch			
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Thin skim coat prior to finished flooring			

REPAIR MORTARS - THIN

FASCO®

Category: Thin/medium patch and screed underlayment
Angle of Use: Horizontal/sloping
Thickness: Featheredge to 1 inch
Set Time: Fast-set
Admix Required: Yes
Bonding Agent Required: Yes
Typical Use: To smooth and slope prior to finished flooring

TYPE	PACKAGE	PER PALLET
Fast Set	40# bag	70

MASCO™

Category: Thin/medium patch and screed underlayment
Angle of Use: Horizontal/sloping
Thickness: Featheredge to 1/2 inch
Set Time: Normal-set
Admix Required: Yes
Bonding Agent Required: Yes
Typical Use: To smooth and slope prior to finished flooring

TYPE	PACKAGE	PER PALLET
Gray	40# bag	70
Light Gray	40# bag	70



REPAIR MORTARS - THIN

PATCHCO®

Category:	Thin/medium patch and screed underlayment	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal/sloping	Fast Set	40# bag	70
Thickness:	Featheredge to 1 inch			
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	To smooth and slope prior to finished flooring			

TDQ Thin Deep Quick Repair™

Category:	Multi-Purpose patch and screed underlayment	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal/vertical/overhead/sloping	Fast Set	50# bag	50
Thickness:	Featheredge to 4 inches	Fast Set	50# pail	36
Set Time:	Fast-set	Fast Set	15# pail	54
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Multi-purpose patch and repairs to all types of concrete			

REPAIR MORTARS - THICK



FASTCRETE®

Category:	Deep patch and screed underlayment
Angle of Use:	Horizontal/sloping
Thickness:	1/8 inch to 3 inches
Set Time:	Fast-set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Filling, screeding and ramping deep areas.

TYPE	PACKAGE	PER PALLET
Fast Set	50# bag	50

MASCRETE®/R-50™

Category:	Deep patch and screed underlayment
Angle of Use:	Horizontal/sloping
Thickness:	1/8 inch to 3 inches
Set Time:	Normal-set
Admix Required:	Yes
Bonding Agent Required:	Yes
Typical Use:	Filling, screeding and ramping deep areas

TYPE	PACKAGE	PER PALLET
Normal Set	50# bag	50

SILPRORAPID™

Category:	Full depth repair
Angle of Use:	Horizontal
Thickness:	1/4 inch to 6 inches
Set Time:	Fast-set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Repairs to highways and bridge decks

TYPE	PACKAGE	PER PALLET
Fast Set	50# bag	50
Fast Set	2500# sack	1

SELF LEVELING CEMENTS

SLU SUPERFLOW™

Category:	Self leveling underlayment	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Fast Set	50# bag	50
Thickness:	1/8 inch to 2 inches			
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	Yes			
Typical Use:	Smoothing substrate prior to finished flooring			

SILFLO® 230/SLT™

Category:	Self leveling underlayment and topping	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Fast Set	50# bag	50
Thickness:	1/8 inch to 5 inches	Fast Set	2500# sack	1
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	Yes			
Typical Use:	Smoothing substrate prior to finished flooring or for a wear surface			

SILFLO® 220

Category:	Self leveling underlayment	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Fast Set	50# bag	50
Thickness:	1/8 inch to 2 inches	Fast Set	2500# sack	1
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	Yes			
Typical Use:	Smoothing substrate prior to finished flooring			

SILFLO® SG

Category:	Self leveling synthetic gypsum underlayment	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Fast Set	50# bag	50
Thickness:	Featheredge to 2 inches	Fast Set	2500# sack	1
Set Time:	Fast-set			
Admix Required:	No			
Bonding Agent Required:	Yes			
Typical Use:	Smoothing gypsum and wood substrates prior to finished flooring			



EPOXY BONDING AGENT AND MOISTURE MITIGATION

CIE 100 EPOXY™

Category:	Epoxy Bonding Agent and Moisture Mitigation
Angle of Use:	Horizontal
Thickness:	n/a
Set Time:	Normal set
Admix Required:	No
Bonding Agent Required:	n/a
Typical Use:	Blocking moisture vapor from concrete substrate and bonding agent for underlayments and toppings

TYPE	PACKAGE	PER PALLET
Normal Set	2 gallon kit	40

VERTICAL & OVERHEAD MORTARS



EASY PATCH®

Category:	Vertical and Overhead patching mortar
Angle of Use:	Horizontal, vertical, overhead
Thickness:	1/8 inch to 2 inches
Set Time:	Fast set
Admix Required:	Depends on application
Bonding Agent Required:	Depends on application
Typical Use:	Patching isolated holes, voids and spalls in concrete

TYPE	PACKAGE	PER PALLET
Fast Set	50# bag	50

SILPROREPAIR® VOH (also available in extended set time version)

Category:	Vertical and Overhead patching mortar
Angle of Use:	Horizontal, vertical, overhead
Thickness:	1/8 inch to 4 inches
Set Time:	Fast set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Patching isolated holes, voids and spalls in concrete

TYPE	PACKAGE	PER PALLET
Fast Set	50# bag	50

VO PATCH®

Category:	Vertical and Overhead patching mortar
Angle of Use:	Horizontal, vertical, overhead
Thickness:	1/8 inch to 4 inches
Set Time:	Fast set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Patching isolated holes, voids and spalls in concrete

TYPE	PACKAGE	PER PALLET
Fast Set	50# bag	50

DECORATIVE EXTERIOR FINISHES



CALIFORNIA STUCCO™

Category:	Stucco
Angle of Use:	Vertical, overhead
Thickness:	1/8 inch to 3/8 inches
Set Time:	Normal set
Admix Required:	Yes
Bonding Agent Required:	Yes
Typical Use:	As decorative façade to walls and building siding

TYPE	PACKAGE	PER PALLET
White	80# bag	40
Gray	80# bag	40

CONCRETE FINISH™

Category:	Stucco
Angle of Use:	Vertical, overhead
Thickness:	1/8 inch to 3/8 inches
Set Time:	Normal set
Admix Required:	Yes
Bonding Agent Required:	Yes
Typical Use:	As decorative façade to walls and building siding

TYPE	PACKAGE	PER PALLET
White	80# bag	40
Gray	80# bag	40

FSB FIBERGLASS SURFACE BONDING CEMENT®

Category:	Structural bonding and base coat
Angle of Use:	Vertical, overhead
Thickness:	1/8 inch to 3/4 inches
Set Time:	Normal set
Admix Required:	Depends on application
Bonding Agent Required:	Depends on application
Typical Use:	Base coat for stucco or structural bonding cement to strengthen masonry

TYPE	PACKAGE	PER PALLET
White	50# bag	50
Gray	50# bag	50

SKIMWALL™

Category:	Concrete Skim Coat
Angle of Use:	Vertical, overhead, horizontal
Thickness:	Featheredge to 1/2 inches
Set Time:	Fast set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Smooth textured decorative skim coat for concrete

TYPE	PACKAGE	PER PALLET
All Colors	15# pail	54
All Colors	25# bag	120

SILPROFINISH COTE™

Category:	Brushable wall finish
Angle of Use:	Vertical, overhead
Thickness:	Featheredge to 1/16 inch
Set Time:	Normal set
Admix Required:	No
Bonding Agent Required:	No
Typical Use:	Coating for uniform appearance over patched concrete

TYPE	PACKAGE	PER PALLET
Gray	25# bag	120



WATERPROOFING CEMENTS

SEAL COTE®

Category:	Waterproofing Cement
Angle of Use:	Vertical, overhead
Thickness:	n/a
Set Time:	Normal set
Admix Required:	Depends on application
Bonding Agent Required:	Depends on application
Typical Use:	Waterproofing interior and exterior of basement walls

TYPE	PACKAGE	PER PALLET
White	50# bag	50
Gray	50# bag	50
White	50# pail	36
Gray	50# pail	36



GROUT

SILPROGROUT® 424

Category:	Non-shrink grout	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal and vertical	Gray	50# bag	50
Thickness:	½ inch to 10 inches			
Set Time:	Normal set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Structural grouting of anchor rods and base plates			

SILPROGROUT® UWR

Category:	Underwater grout	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal and vertical	Gray	50# bag	50
Thickness:	¾ inch to 8 inches			
Set Time:	Normal set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Structural repair of underwater piles and columns			

HYDRAULIC PLUGS

EASY PLUG® (available in 3-5 minute and 60 second set time versions)

Category:	Hydraulic Plug	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal, vertical and overhead	Gray	10# can	144
Thickness:	minimum ¾ inch	Gray	50# pail	36
Set Time:	Fast set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Stopping flowing water from cracks and holes.			

POLYMERIC JOINT SANDS

SILPROPAVER® SAND

Category:	Polymeric Joint Sand	TYPE	PACKAGE	PER PALLET
Angle of Use:	Horizontal	Beige	50# bag	63
Thickness:	maximum 4 inches	Gray	50# bag	63
Set Time:	Normal set			
Admix Required:	No			
Bonding Agent Required:	No			
Typical Use:	Filling paver and stone joints for walkways, patios, etc.			

BONDING AGENTS & ADMIXTURES



C-21 ALL ACRYLIC®/R-50 LATEX™

Category:	Acrylic Bonding Agent and Admix
Angle of Use:	n/a
Thickness:	n/a
Set Time:	Normal set
Admix Required:	n/a
Bonding Agent Required:	n/a
Typical Use:	Bonding agent and admix for cement based mortars and coatings

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36
Liquid	55 Gallon	4

CONCRETE SUPPLEMENT™

Category:	Anti-freeze for concrete and mortar
Angle of Use:	n/a
Thickness:	n/a
Set Time:	Normal set
Admix Required: :	n/a
Bonding Agent Required:	n/a
Typical Use::	Additive to concrete and mortar for use in low
:	temperatures

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36
Liquid	55 Gallon	4
Liquid	275 Gallon	1



Mortar Mixed With Water
after 25 cycles of Freeze/Thaw Testing



Mortar Mixed With **CONCRETE SUPPLEMENT™**
after 25 cycles of Freeze/Thaw Testing

R-2000 PRIMER™

Category:	Primer for bonding self-leveling
Angle of Use:	horizontal
Thickness:	n/a
Set Time:	1-3 hours
Admix Required:	n/a
Bonding Agent Required:	n/a
Typical Use:	Bonding agent for self-leveling underlayments and toppings

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36
Liquid	50 Gallon	4

BONDING AGENTS & ADMIXTURES

R-3000 PRIMER™

Category:	Primer for bonding self-leveling	TYPE	PACKAGE	PER PALLET
Angle of Use:	horizontal	Liquid	1 Gallon	144
Thickness:	n/a			
Set Time:	1-3 hours			
Admix Required:	n/a			
Bonding Agent Required:	n/a			
Typical Use:	Bonding agent for self-leveling underlayments and toppings over non porous substrates			

WELD-O-BOND™

Category:	Bonding agent for concrete and plaster	TYPE	PACKAGE	PER PALLET
Angle of Use:	horizontal	Liquid	1 Gallon	144
Thickness:	n/a	Liquid	5 Gallon	36
Set Time:	1-3 hours	Liquid	55 Gallon	4
Admix Required:	n/a			
Bonding Agent Required:	n/a			
Typical Use:	Bonding agent for new concrete over old concrete			



MASONRY LUSTA PLUS® GLOSS AND MATTE

Category:	Decorative Sealer
Angle of Use:	horizontal, vertical
Thickness:	n/a
Set Time:	12-24 hours
Admix Required:	n/a
Bonding Agent Required:	n/a
Typical Use:	Sealer for masonry to provide dark, wet look

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36

SILOCKS PLUS®

Category:	Clear, penetrating sealer
Angle of Use:	horizontal, vertical
Thickness:	n/a
Set Time:	12-24 hours
Admix Required:	n/a
Bonding Agent Required:	n/a
Typical Use:	Non-visible sealer for masonry and concrete

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36

SILOCKS PLUS® WB

Category:	Clear, water-based, penetrating sealer
Angle of Use:	horizontal, vertical
Thickness:	n/a
Set Time:	12-24 hours
Admix Required:	n/a
Bonding Agent Required:	n/a
Typical Use:	Non-visible sealer for masonry and concrete

TYPE	PACKAGE	PER PALLET
Liquid	1 Gallon	144
Liquid	5 Gallon	36

SILPRO LLC
2 NEW ENGLAND WAY
AYER, MA 01432-1514

TELEPHONE: 978-772-4444
TOLL FREE: 800-343-1501
FACSIMILE: 978-772-7456
EMAIL: INFO@SILPRO.COM

WWW.SILPRO.COM



SILPRO