

CENTRAL APPALACHIA REGION PENNSYLVANIA / WEST VIRGINIA

PENNSYLVANIA

SilproRapid™

679.2 (a) Rapid Set Concrete Patching Materials-Type 2

SilproGrout 424

1080.2 (c) Nonshrink Grout (Cement-Based)

WEST VIRGINIA

SilproRapid™

Concrete Patching Materials 715.4.1 and 715.4.2

SilproRepair™ VOH

Concrete Patching Materials 715.4.1 and 715.4.2

SilproGrout 424

Non Shrink Grout 715.5

SILPRO

SilproRapid™

PERFORMANCE CHARACTERISTICS

- Structural Full-Depth Repair Mortar
- Low Permeability (Extended)
- Fast-Setting
- Cement-Based
- One Component
- Non-Shrink
- Open to vehicle traffic in as little as 1 hour (at 73°F)
- No added chlorides

50 lb \$ _____

SILPRO

SilproRepair™ VOH

PERFORMANCE CHARACTERISTICS

- Structural Vertical and Overhead Application
- Freeze/Thaw Resistant
- Corrosion Inhibitor
- Low Permeability
- One-Component
- Fiber Reinforced
- Up to 4" Per Lift
- Rapid-Setting

50 lb \$ _____

SILPRO

SilproGrout® 424

PERFORMANCE CHARACTERISTICS

- Structural
- Non-Shrink
- Non-Metallic
- High-Strength
- Cement-Based
- Non-Corrosive
- High Performance

50 lb \$ _____