

NEW YORK-NEW JERSEY REGION NEW YORK / NEW JERSEY

NEW YORK

SilproRapid™

Concrete Repair Material (701-04) • Rapid Hardening Concrete Repair Material (Normal Weather) (701-09)

SilproRepair VOH

Vertical and Overhead Patching Materials (701-08)

NEW JERSEY

SilproRapid™

Quick Setting Patch, Type 1 903.07

SilproRepair™ VOH

Quick Setting Patch, Type 2 903.07

SilproGrout 424

Grout, Non-Shrink 903.08

SILPRO

SilproRapid™

PERFORMANCE CHARACTERISTICS

- Structural Full-Depth Repair Mortar
- Low Permeability (Extended)
- Fast-Setting
- Cement-Based
- One Component
- Non-Shrink
- Open to vehicle traffic in as little as 1 hour (at 73°F)
- No added chlorides

50 lb \$ _____

SILPRO

SilproRepair™ VOH

PERFORMANCE CHARACTERISTICS

- Structural Vertical and Overhead Application
- Freeze/Thaw Resistant
- Corrosion Inhibitor
- Low Permeability
- One-Component
- Fiber Reinforced
- Up to 4" Per Lift
- Rapid-Setting

50 lb \$ _____

SILPRO

SilproGrout® 424

PERFORMANCE CHARACTERISTICS

- Structural
- Non-Shrink
- Non-Metallic
- High-Strength
- Cement-Based
- Non-Corrosive
- High Performance

50 lb \$ _____