

NORTHERN NEW ENGLAND REGION MAINE / NEW HAMPSHIRE / VERMONT

MAINE

SilproRapid™

Rapid Set Concrete Patch Materials

SilproRepair™ VOH

Rapid Set Concrete Patch Materials

SilproGrout 424

Grouts

NEW HAMPSHIRE

SilproRapid™

QPL 520.A Rapid-Hardening Patching Material

SilproRepair™ VOH

QPL 550.A Fast Setting Grouts for Anchor Bolts • QPL 609.A Non-Shrink Non Metallic Grout

VERMONT

SilproRapid™

APL 780.01 (c) Concrete Repair Material, Type III

SilproRepair™ VOH

APL 780.01 (a) Concrete Repair Material, Type I

SilproGrout 424

APL 707.03 Mortar, Type IV • APL 707.01 (c) (1) Mortar, Type IV, Prepackaged

SILPRO

SilproRapid™

PERFORMANCE CHARACTERISTICS

- Structural Full-Depth Repair Mortar
- Low Permeability (Extended)
- Fast-Setting
- Cement-Based
- One Component
- Non-Shrink
- Open to vehicle traffic in as little as 1 hour (at 73°F)
- No added chlorides

50 lb \$ _____

SILPRO

SilproRepair™ VOH

PERFORMANCE CHARACTERISTICS

- Structural Vertical and Overhead Application
- Freeze/Thaw Resistant
- Corrosion Inhibitor
- Low Permeability
- One-Component
- Fiber Reinforced
- Up to 4" Per Lift
- Rapid-Setting

50 lb \$ _____

SILPRO

SilproGrout® 424

PERFORMANCE CHARACTERISTICS

- Structural
- Non-Shrink
- Non-Metallic
- High-Strength
- Cement-Based
- Non-Corrosive
- High Performance

50 lb \$ _____